


### LÍNEA PINS LSI / I



CÓDIGO	MODELO	LONGITUD MM.	MILLARES ESTUCHE	MILLARES EMBALAJE
9022.9	LSI / I - 15	15	17	204
9022.10	LSI / I - 20	20	10	102
9022.11	LSI / I - 25	25	8,5	102
9022.12	LSI / I - 30	30	8,5	102



#### CLAVADORA SIMB12-AX

EMPLEA CLAVO 1,2 LSI/I DE 15 a 50mm.  
NEUMÁTICA, PRESIÓN: 5 a 7 ATM.  
CÓDIGO: 1247.55

### LÍNEA BRAD 1,53



CÓDIGO	MODELO	LONGITUD MM.	MILLARES ESTUCHE	MILLARES EMBALAJE
9022.18	BRAD 1,53 / 14 - 20	20	6	60
9022.19	BRAD 1,53 / 14 - 25	25	4	40
9022.20	BRAD 1,53 / 14 - 30	30	4	40
9022.21	BRAD 1,53 / 14 - 35	35	2,4	24
9022.22	BRAD 1,53 / 14 - 40	40	2,4	24
9022.23	BRAD 1,53 / 14 - 45	45	2,4	24
9022.24	BRAD 1,53 / 14 - 50	50	2	20
9022.25	BRAD 1,53 / 14 - 55	55	2	20
9022.79	BRAD 1,53 / 14 - 60	60	2	20



#### CLAVADORA SIMB153

EMPLEA CLAVO 1,53 O 14 DE 20 a 64mm.  
NEUMÁTICA, PRESIÓN: 6 a 8 ATM.  
CÓDIGO: 1247.56

